

Application

Beam style	asymmetric flood
Suitable for	small-scale theatre, batten cyclorama lighting
Specification level	professional range
Typical throw distance	2 - 5m

Electrical specifications

Supply Volts	230/240V AC single phase
Max. Lamp Watts	500W
Lamp base	R7s
Auto-disconnect	no
Cable/connection	1.5m, 3 x 1.5mm ² flexible cable to bare ends
Standards Compliance	EN60598-2-17, CE marked

Mechanical specifications

Paint/Finish	black/silver/white epoxy powder paint
Lamp House Construction	1-compartment, may be coupled together with identical units to create a 2/3/4 compartment batten, available accessories for domino assembling.
Reflector	asymmetrical, aluminium
Mounting & suspension	supplied without stirrup- see list of separate hanging accessories available
Weight/Packed weight	1,8kg / 4,3kg (2 units in a box)
Packed volume	0.021m ³ (2 units in a box)
Filter cut size	244 x 195mm
Accessory runners	3 slots
Safety guard/glass	optional accessory
Colour frame	metal, 244 x 195mm supplied
Lamp access	front access

Operational specifications

Working position	max. tilting $\pm 180^\circ$ from vertical
Positional adjustment	tilt lock on one side when mounted in batten

Lamp types

200W	K11 R7s 230/240V 3200K 2.000 hrs
300W	K9 R7s 230/240V 3200K 2.000 hrs
500W	K1 R7s 230/240V 3200K 2.000 hrs

LDR recommends Philips lamps

Accessories

Lamps	see above		
Spare metal colour frame	■20100120	□20100120B	■20100120C
3-leaf barndoor	■20100620	□20100620B	■20100620C
	□■20100620D		■20100620E
2-leaf barndoor	■20100520	□20100520B	■20100520C
	□■20100520D		■20100520E
Clear safety glass	20101420	Safety guard	20100220
Kit for square mounting	20101920		
Stirrup kit 1 Rima	20102621	Kit linear mounting 2 Rima	20102622
Kit linear mounting 3 Rima	20102623	Kit linear mounting 4 Rima	20102624
Hook clamp	20100900		
Safety bond	20101200		

Photometric data

Horizontal											K1
Beam dia.	3.1	4.7	6.3	7.8	9.4	10.9	12.5	14.1	15.6	m	
lux	1585	704	396	254	176	129	99	78	63		
Distance	2	3	4	5	6	7	8	9	10	m	

Vertical											
Beam dia.	1.9	2.9	3.8	4.8	5.7	6.7	7.6	8.6	9.5	m	
lux	2151	956	538	344	239	176	134	106	86		
Distance	2	3	4	5	6	7	8	9	10	m	


LUCI DELLA RIBALTA PROFESSIONAL LIGHTING PRODUCTS

rima[®] A500 no stirrup

200 - 500W

asymmetric floodlight

part number: ■ 10506150 □ 10506151 ■ 10506152



New, stylish and high specification 500W asymmetrical floodlights, ideal for professional usage in all cyclorama-type lighting applications.

The modular design enables several units to be coupled together to form a single compartment or square batten. Improved design prevents any light spill. A colour frame and 1.5m mains cable are included in standard delivery.

Available to special order with extended front chassis for longer gel life.



Luci della Ribalta srl
Via Berna 14
46042 Castel Goffredo (MN), Italy
tel: +39 0376 771777
fax: +39 0376 772140
www.ldr.it info@ldr.it

issue: ap ©2008. LDR reserves the right to alter the specification without prior notice.