

RIMA A 500

with stirrup / con forcilla ■ 10506050 Black □ 10506051 White ■ 10506052 Silver
without stirrup / senza forcilla ■ 10506150 Black □ 10506151 White ■ 10506152 Silver

ACCESSORIES

20100120
colour frame, black
20100120B
colour frame, white
20100120C
colour frame, silver
20100220
safety guard, black
20100420
4-leaf barndoor, black
20100420B
4-leaf barndoor, white
20100420C
4-leaf barndoor, silver
20100420D
4-leaf barndoor, white/black
20100420E
4-leaf barndoor, silver/black
20100520
2-leaf barndoor, black
20100520B
2-leaf barndoor, white
20100520C
2-leaf barndoor, silver
20100520D
2-leaf barndoor, white/black
20100520E
2-leaf barndoor, silver/black
20100620
3-leaf barndoor, black
20100620B
3-leaf barndoor, white
20100620C
3-leaf barndoor, silver
20100620D
3-leaf barndoor, white/black
20100620E
3-leaf barndoor, silver/black
20101420
safety glass
20101920
kit for square mounting
20102621
stirrup kit 1 Rima
20102622
kit for linear mounting 2 Rima
20102623
kit for linear mounting 3 Rima
20102624
kit for linear mounting 4 Rima
20100900
hook clamp
20101200
safety bond




COMPATIBLE LAMPS

K11 R7s 200W 230V/240V 3200°K 2000 hrs
K9 R7s 300W 230V/240V 3200°K 2000 hrs
K1 R7s 500W 230V/240V 3200°K 2000 hrs

• LDR recommends Philips lamps

PRODUCT SPECS

reflector
aluminium, asymmetrical
microswitch
no
colour frame
244x195mm
throw
2-5m
weight
2,0kg



Stylish and high specification 500W asymmetrical floodlights, ideal for professional usage in all cyclorama-type lighting applications. Rima A500F is designed for usage as single module flood, but a large choice of different models and accessories is available for the creation of multiple rows or square-battens. Rima A500 is delivered complete with colour frame and 1.5m mains cable.

Diffusore asimmetrico da 500W, di linea gradevole e di elevata resa ottica.

E' la scelta ideale per l'illuminazione omogenea di fondali e parti di scena da angolature oblique, anche in ambito professionale. Rima A500F è la versione a modulo singolo, ma è disponibile un'ampia scelta di altri modelli ed accessori per il montaggio modulare.

Viene fornito di serie completo di telaio portagelatina e 1.5m cavo di alimentazione.

Available to special order with extended front chassis for longer gel life.

Su richiesta disponibile anche con telaio anteriore esteso per gelatine dai colori saturi.



PHOTOMETRIC DATA

K1

HORIZONTAL	m ∅	3,1	4,7	6,3	7,8	9,4	10,9	12,5	14,1	15,6
	lux	1.585	704	396	254	176	129	99	78	63
VERTICAL	m →	2	3	4	5	6	7	8	9	10
	m ∅	1,9	2,9	3,8	4,8	5,7	6,7	7,6	8,6	9,5
	lux	2.151	956	538	344	239	176	134	106	86
	m →	2	3	4	5	6	7	8	9	10