

Digital Dimmer Pack DDP610 S400



Digital dimmer pack DDP610 S400 is designed to fulfill all the requirements of the most demanding lighting applications e.g. theatre, live concerts and also permanent installations. Six channels touring dimming unit with same control as DDP12xx S400 devices. With 2U size and 400us chokes and 5 year standard guarantee is best buy dimming unit.



- 6 x 10 A dimming channels
- Risetime 400 uS
- Quick setting with encoder + 2 buttons
- User-friendly menu structure
- Measurement of main voltage, Temperature & DMX line
- Patch with each input
- Preheat for each channel
- Curve for each channel
- Manual control
- Electronic lock-out
- Dimming – phase-angle control
- Load check for each channel
- Temperature controlled fan
- Short-circuit protected by circuit breakers
- Variable outputs connectors

DMX input with TRUE output

USITT DMX 512 (1990)

Input is protected by transil diodes – high voltage protection by clamping action (peak power 600W, 10/1000us)

Power supply

3 x 230V – 50Hz

Temperature of use

–20...65°C

Dimensions

Steel housing with powder coating

462 x 88 x 300 mm


Weight

DDP610

13kg

XLR 5 pin connector (Neutrik®)

Pin 1	GND
Pin 2	Data –
Pin 3	Data +
Pin 4,5	Not connected



Maximum Load

2300 W

Output connectors

- RM7.5 Screw Terminal box



- 6 x Schuko



- Socapex 19



- ILME 16

