SUONO PC 650 PLUS

■ 10602010 *Black* □ 10602011 *White* ■ 10602012 *Silver*

ACCESSORIES

20100103
colour frame, black
20100103B
colour frame, white
20100103C
colour frame, silver
20100203
safety guard, black
20100203B
safety guard, white
20100203C
safety guard, silver
20100303
4-leaf barndoor, black
20100303B
4-leaf barndoor, white
20100303C
4-leaf barndoor, silver
20100303D
4-leaf barndoor, white/black
20100303E
4-leaf barndoor, silver/black
20100900
hook clamp
20101100
alu-grip clamp
20101200
safety bond
20106013
colour scroller Xpress 13



PRODUCT SPECS

lens type
120mm dia. pebble-convex
reflector
55mm dia. glass
microswitch
double-pole
colour frame
150x150mm
throw
2-10m
beam angle
7°-58°
weight
4,3kg

Quality 500/650W PC spotlight ideal for professional usage in smaller venues. The well-defined beam is adjustable by a screw-focus mechanism, and the design also includes a hinged lamp-tray and a double-microswitch interlock for safe lamp replacement.
A colour frame, safety guard and 1.5m mains cable are all included as standard.

Illuminatore piano-convesso da 500/650W per uso professionale su piccole scene. Produce un fascio di luce molto omogeneo.
E' dotato di carrello portalampada basculante ad apertura frontale e di doppio microinterruttore di sicurezza.
Fornito di serie completo di telaio portagelatina, rete di protezione e 1.5m cavo di alimentazione.

PHOTOMETRIC DATA T27

SPOT	m ø	0,2	0,4	0,5	0,6	0,7	0,9	1,0	1,1	1,2
	lux	24.800	11.022	6.200	3.968	2.756	2.024	1.550	1.225	992
	m →	2	3	4	5	6	7	8	9	10
FLOOD	m ø	2,2	3,3	4,4	5,5	6,7	7,8	8,9	10,0	11,1
	lux	2.148	955	537	344	239	175	134	106	86
	m →	2	3	4	5	6	7	8	9	10

COMPATIBLE LAMPS

M38 GY9.5 300W 230V/240V 2950°K 2000hrs
M40 GY9.5 500W 230V/240V 2950°K 2000hrs
T18 GY9.5 500W 230V/240V 3000°K 360hrs
T25 GY9.5 500W 230V/240V 3000°K 360hrs
T26 GY9.5 650W 230V/240V 3050°K 600hrs
T27 GY9.5 650W 230V/240V 3050°K 600hrs

• LDR recommends Philips lamps